

Electric Circuits I

Laboratory 1: Vectors and Matrices MATLAB

Objective:

- In this laboratory you will learn how to represent and use vectors and matrices in MATLAB.

A. Background notes:

In MATLAB an $M \times N$ matrix is a rectangular array of numbers with M rows and N columns. It can be defined by typing the matrix elements between square brackets. Elements along a row are separated by commas, and rows are separated by semi colons.

In Lab 0, you used row vectors for values of the angle and time variable. A row vector is a matrix with $M1$.

In MATLAB Help, go to the Mathematics chapter. The second section is “Matrices in MATLAB.” Read the first four sections about creating, adding, and multiplying matrices.

B. Matrix Multiplication:

- Create 2 x 2 matrices A and B are as follows:

$$A = [2,1; 3,2] \text{ and } B=[3,1; 2,2]$$

- Print A' and B' , the transposes of these two matrices.
- Compute the following 4 matrix products and print them. Are any the same? Which ones?
 $A1 = A * B$, $A2 = B * A$, $A3 = (A' * B)'$, $A4 = (B' * A)'$

C. Matrix Inverses:

- Use “inv” to compute the following matrix inverses:
 $A1 = \text{inv}(A * B)$, $A2 = \text{inv}(A) * \text{inv}(B)$, $A3 = \text{inv}(B * A)$, $A4 = \text{inv}(B) * \text{inv}(A)$.
- Check the inverse values. Multiply $A1*(A*B)$ and also multiply $(A*B)*A1$. What are the two products?

D. Solving Circuits with MATLAB:

The result of a KVL/KCL analysis of a circuit is the set of simultaneous equations:

$$\begin{aligned} V_1 + V_3 &= 10 \\ 3V_1 + 3V_2 + 4V_3 &= 12 \\ 2V_1 + 2V_2 + 3V_3 &= 5 \end{aligned}$$

which can be written using matrices as follows:

$$\begin{bmatrix} 1 & 0 & 1 \\ 3 & 3 & 4 \\ 2 & 2 & 3 \end{bmatrix} \begin{bmatrix} V_1 \\ V_2 \\ V_3 \end{bmatrix} = \begin{bmatrix} 10 \\ 12 \\ 5 \end{bmatrix} = C * V = S$$

$$C = \begin{bmatrix} 1 & 0 & 1 \\ 3 & 3 & 4 \\ 2 & 2 & 3 \end{bmatrix}, \quad V = \begin{bmatrix} V_1 \\ V_2 \\ V_3 \end{bmatrix}, \quad S = \begin{bmatrix} 10 \\ 12 \\ 5 \end{bmatrix}$$

To solve this 3x3 system of equations we invert the coefficient matrix **C** and multiply it by the source matrix **S**.

- Invert the matrix **C** and solve the system for the voltage matrix **V**. Then verify that the result is correct by multiplying **C*V** and compare the result with **S**.

E. Solving a System of Linear Equations with Symbolic Toolbox

MATLAB or Octave has a toolbox to simplify symbolically equations. As shown in Part D, in order to solve a system of linear equations, the coefficients of equations are simplified and arranged in the order of the unknown ($V_1, V_2, V_3, \dots, V_4$). Once equations are simplified and arranged in order of the known, we can generate coefficient matrix **C** and source vector **S** to solve for the unknown. The simplifying process of coefficients, however, can be tedious with chances of errors. Here, the symbolic tool performs the simplifying process and generate automatically coefficient matrix **C** and source vector **S**. Consider the following equations:

$$\frac{v_a - v_b}{R_1} - I_{s1} + \frac{v_a - v_d}{R_2} - I_{s3} = 0$$

$$\frac{v_b - v_a}{R_1} + I_{s1} + \frac{v_d - v_a}{R_2} + \frac{v_b}{R_3} + I_{s2} + \frac{v_d}{R_4} = 0$$

$$v_b - v_c = V_{s1}$$

$$v_d - v_c = V_{s2},$$

where v_a, v_b, v_c and v_d are unknown variables and others are known with values: $V_{s1} = 6V$, $V_{s2} = 12V$, $I_{s1} = 2mA$, $I_{s2} = 4mA$, $I_{s3} = 6mA$, $R_1 = 1k\Omega$, $R_2 = 1k\Omega$, $R_3 = 2k\Omega$, and $R_4 = 1k\Omega$.

- Create a command script file (.m) using the method shown in Lab0.
- Enter the values for known variables:

```
Vs1 = 6;
Vs2 = 12;
% Is1 = 2mA
Is1 = sym(2)/1e3;
...
R1 = 1e3;
```

- ...;
- Define symbolic unknown variables:

```
syms Va Vb Vc Vd real
```

- Enter equations above:

```
eq1 = (Va-Vb)/R1 - Is1 ... == 0;
```

```
eq2 = ... == 0;
```

```
eq3 = ... == Vs1;
```

```
eq4 = ... == Vs2;
```

- Enter equations and variables:

```
eqns = [eq1, eq2, eq3, eq4];
```

```
vars = [Va, Vb, Vc, Vd];
```

- Use MATLAB or Octave functions to simplify coefficients and generate coefficient matrix **C** and source vector **S**:

```
[C, S] = equationsToMatrix(eqns, vars)
```

- Use the coefficient matrix **C** and the source vector **S** to solve for the unknown variables:

```
v = inv(C) * S
```

- Save the command script file and run it. If there is no error in the command script, the final results will be:

C =	S =	V =
[1/500, -1/1000, 0, -1/1000]	1/125	13/3
[-1/500, 3/2000, 0, 1/500]	-3/500	-8/3
[0, 1, -1, 0]	6	-26/3
[0, 0, -1, 1]	12	10/3

- Create another command script file (.m) and use similar commands to solve for a system of equations below:

$$-I_{s1} + \frac{v_a - v_b}{R_1} + \frac{v_d - v_c}{R_2} + \frac{v_d}{R_5} + \frac{v_d}{R_3 + R_6} = 0$$

$$\frac{v_b - v_a}{R_1} + I_{s2} + \frac{v_c}{R_4} + \frac{v_c - v_d}{R_2} = 0$$

$$v_c - v_b = V_s$$

$$v_d - v_a = 2v_c$$

where v_a, v_b, v_c and v_d are unknown variables and others are known with values: $V_s = 12\text{V}$, $I_{s1} = 4\text{mA}$, $I_{s2} = 2\text{mA}$, $R_1 = 1\text{k}\Omega$, $R_2 = 1\text{k}\Omega$, $R_3 = 1\text{k}\Omega$, $R_4 = 1\text{k}\Omega$, $R_5 = 1\text{k}\Omega$, and

$$R_6 = 1k\Omega.$$

- Compare your results with the expected results:

C =	S =	v =
[1/1000, -1/1000, -1/1000, 1/400]	1/250	-100/7
[1/1000, -1/1000, 1/500, -1/1000]	-1/500	2
[0, -1, 1, 0]	12	14
[-1, 0, -2, 1]	0	96/7

F. More About Matrix Inverses:

- Find the inverse of the matrix D shown below:

$$D = [2,4; 1,2]$$
 - Is there an inverse of D?
 - If the answer is 'NO' then why not?

G. Products of Time Functions:

Given the following functions,

$$p(t) = 5\cos(2\pi 3t) \text{ and } v(t) = 5 * e^{-0.5t}$$

- plot p(t) and v(t) from t = 0 to t=10 using time steps of 0.01 (*Note: e^t is encoded as exp(t)*).

Create the point by point product function b(t) = p(t)v(t) using b=p.*v and plot it. Note that the .* operation multiplies the two vectors point by point rather than computing a matrix product.

Note: Please show all your work.